

Certificate of Analysis No. CA15029

Product: Eichrom's UTEVA® Resin

Lot #: UTA020315

Eichrom's UTEVA® Resin Lot # UTA020315 has been manufactured according to Eichrom's standard operating procedures. This lot has been tested in accordance with Eichrom's quality assurance policy and procedures. This lot of product meets all Eichrom quality specifications.

ANALYSIS RESULTS

Test Value	Specification	Result
Appearance	White beads	Pass
Distribution Ratio, 3.1 N nitric acid	>100	159
% ²³⁰ Th stripped in 5M HCl/0.05M oxalic acid		
Least acceptable mean (4 rep)	90.0	98.8
Max. standard deviation	10.0	3.2
% ²³⁰ Th stripped in 1M HCl		
Maximum acceptable mean (5 rep)	0.5	0.1
Max. standard deviation	1.0	0.0
% ²³³ U stripped in 1M HCl		
Least acceptable mean (5 rep)	90.0	97.5
Max. standard deviation	10.0	2.9
% ²³³ U stripped in 5M HCl/0.05M oxalic acid		
Maximum acceptable mean (5 rep)	1.0	0.1
Max. standard deviation	1.0	0.0
Raw support resin flow rate, mL/min	0.60-0.80	0.66

Sarah Tejchma Quality Manager February 27, 2015

27 FUD 15

Eichrom Technologies LLO 1955 University Lane, Lisle, IL 60532, USA www.eichrom.com

