

Certificate of Analysis No. CA09152

Product: Eichrom's UTEVA® Resin cartridges

Lot #: UTSR09I

Eichrom's UTEVA® Resin cartridge Lot # UTSR09I has been manufactured according to Eichrom's standard operating procedures. The resin used to manufacture this lot has been tested in accordance with Eichrom's quality assurance policy and procedures. This lot of product meets all Eichrom quality specifications.

ANALYSIS RESULTS

<u>Test Value</u>	Specification	Result
Appearance	White beads	Pass
Distribution Ratio, 3.1 N nitric acid	>100	158
% ²³⁰ Th stripped in 5M HCl/0.05M oxalic acid		
Least acceptable mean (4 rep)	90.0	97.7
Max. standard deviation	10.0	8.2
% ²³⁰ Th stripped in 1M HCl		
Maximum acceptable mean (4 rep)	0.5	0.4
Max. standard deviation	1.0	0.1
% ²³³ U stripped in 1M HCl		
Least acceptable mean (4 rep)	90.0	94.9
Max. standard deviation	10.0	3.5
% ²³³ U stripped in 5M HCl/0.05M oxalic acid		
Maximum acceptable mean (4 rep)	1.0	0.1
Max. standard deviation	1.0	0.0

Jill Bryant

Quality System Coordinator

October 26, 2009